



## O-Ring EPDM/FKM

### Ausführung:

- Für ecoFIT, PROGEF Std/Plus, SYGEF Std Verschraubungen und Stumpfschweissmuffen
- Härte ca: 65° Shore
- EPDM minimale Temperatur: -40°
- FKM minimale Temperatur: -15°C

| d<br>(mm) | DN<br>(mm) | EPDM<br>Code | FKM<br>Code | Gewicht<br>(kg) | D<br>(mm) | D1<br>(mm) | D2<br>(mm) |
|-----------|------------|--------------|-------------|-----------------|-----------|------------|------------|
| 20        | 15         | 748 410 006  | 749 410 006 | 0.002           | 27.28     | 20.22      | 3.53       |
| 25        | 20         | 748 410 007  | 749 410 007 | 0.002           | 35.23     | 28.17      | 3.53       |
| 32        | 25         | 748 410 008  | 749 410 008 | 0.003           | 39.99     | 32.93      | 3.53       |
| 40        | 32         | 748 410 009  | 749 410 009 | 0.003           | 51.33     | 40.65      | 5.34       |
| 50        | 40         | 748 410 010  | 749 410 010 | 0.004           | 57.68     | 46.99      | 5.34       |
| 63        | 50         | 748 410 011  | 749 410 011 | 0.005           | 70.37     | 56.69      | 5.34       |
| 75        | 65         | 748 410 013  | 749 410 013 | 0.006           | 79.90     | 69.22      | 5.34       |
| 90        | 80         | 748 410 014  | 749 410 014 | 0.007           | 92.60     | 81.92      | 5.34       |
| 110       | 100        | 748 410 015  | 749 410 015 | 0.008           | 111.68    | 101        | 5.34       |

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: [info.ps@georgfischer.com](mailto:info.ps@georgfischer.com)

Internet: <http://www.gfps.com>