



Profil-Flanschdichtung EPDM/FKM Metrisch

Ausführung:

- Passend zu allen metrischen GF Bundbuchsen und Vorschweissbunden
- Härte: 70° Shore **EPDM**, 75° Shore **FKM**
- **EPDM**: DVGW geprüft nach Merkblatt Wasser W 270, KTW-Empfehlung
- Zentrierung über Innendurchmesser Schraubenkranz
- Werkstoff Stahleinlage: Kohlenstoffstahl
- Gummi-Stahl Körper kombiniert mit Gummi Profil-Dichtschnur bis d630
- Gummi-Stahl-Körper ideal für grosse Dimensionen (d710 - d1000)

di VSB/BB zeigt die passenden Innendurchmesser der Vorschweissbunde/Bundbuchsen

d (mm)	D (mm)	di VSB/BB (mm)	D1 (mm)	DN (mm)	PN (bar)	EPDM Code	FKM Code	Gewicht (kg)	H (mm)	H1 (mm)
16	46	6 - 16	16	10	16	748 440 705	749 440 705	0.012	4	3
20	51	10 - 20	20	15	16	748 440 706	749 440 706	0.013	4	3
25	61	12 - 22	22	20	16	748 440 707	749 440 707	0.014	4	3
32	71	18 - 28	28	25	16	748 440 708	749 440 708	0.019	4	3
40	82	30 - 40	40	32	16	748 440 709	749 440 709	0.026	4	3
50	92	36 - 46	46	40	16	748 440 710	749 440 710	0.039	4	3
63	107	48 - 58	58	50	16	748 440 711	749 440 711	0.050	5	4
75	127	59 - 69	69	65	16	748 440 712	749 440 712	0.082	5	4
90	142	73 - 84	84	80	16	748 440 713	749 440 713	0.083	5	4
110	162	94 - 104	104	100	16	748 440 714	749 440 714	0.127	6	5
125	162	113 - 123	123	100	16	748 440 715	749 440 715	0.105	6	5
140	192	127 - 137	137	125	16	748 440 716	749 440 716	0.173	6	5
160 - 180	218	150 - 160	160	150	16	748 440 717	749 440 717	0.207	8	6
200	273	192 - 203	203	200	16	748 440 719	749 440 719	0.263	8	6
225	273	207 - 220	220	200	16	748 440 720	749 440 720	0.255	8	6
250	328	238 - 252	252	250	16	748 440 721	749 440 721	0.462	8	6
280	328	264 - 274	274	250	16	748 440 722	749 440 722	0.323	8	6
315	378	296 - 306	306	300	16	748 440 723	749 440 723	0.549	8	6
355	438	340 - 355	355	350	16	748 440 724	749 440 724	0.870	10	7
400	489	385 - 400	400	400	16	748 440 725	749 440 725	1.088	10	7
450	594	393 - 403	403	500	10	748 440 726	749 440 726	0.718	10	7
500	594	437 - 447	447	500	10	748 440 727	749 440 727	0.718	10	7
560	695	484 - 494	494	600	10	748 440 728	749 440 728	0.923	10	7
630	695	545 - 555	555	600	10	748 440 729	749 440 729	0.923	10	7
710	810	562 - 712	712	700	6	748 440 730		0.890	6	3
800	917	663 - 813	813	800	6	748 440 731		1.340	6	3
900	1017	765 - 915	915	900	6	748 440 732		1.170	6	3
1000	1124	866 - 1016	1016	1000	6	748 440 733		1.360	6	3

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>