



ecoFIT T 90° reduziert PE100 d63-250mm / SDR11

Ausführung:

- Werkstoff: PE100
- Konventionelle Stumpfschweissung nach DVS 2207
- IR = Infrarot (IR Plus) kompatibel. Zu verschweißen mit Parameter PE100

d	DN	PN	SDR	d1	SM	Code	Gewicht	PF
(mm)	(mm)	(bar)		(mm)			(kg)	
63	50	16	11	32	IR	753 208 351	0.161	2 68 240 017
63	50	16	11	50	IR	753 208 352	0.180	2 68 240 017
75	65	16	11	32	IR	753 208 353	0.255	2 68 240 017
75	65	16	11	50	IR	753 208 354	0.265	2 68 240 017
75	65	16	11	63	IR	753 208 355	0.278	2 68 240 017
90	80	16	11	50	IR	753 208 357	0.435	2 68 240 017
90	80	16	11	63	IR	753 208 358	0.448	2 68 240 017
90	80	16	11	75	IR	753 208 359	0.462	2 68 240 017
110	100	16	11	32	IR	753 208 360	0.685	2 68 240 017
110	100	16	11	50	IR	753 208 361	0.694	2 68 240 017
110	100	16	11	63	IR	753 208 362	0.709	2 68 240 017
110	100	16	11	75	IR	753 208 363	0.717	2 68 240 017
110	100	16	11	90	IR	753 208 364	0.734	2 68 240 017
160	150	16	11	63	IR	753 208 371	2.269	2 68 240 017
160	150	16	11	75	IR	753 208 372	2.255	2 68 240 017
160	150	16	11	90	IR	753 208 373	2.317	2 68 240 017
160	150	16	11	110	IR	753 208 374	2.353	2 68 240 017
225	200	16	11	90	IR	753 208 388	4.759	2 68 240 017
225	200	16	11	110	IR	753 208 389	4.796	2 68 240 017
225	200	16	11	160	IR	753 208 391	4.854	2 68 240 017
250	250	16	11	110		753 221 031	8.120	2 51 301 004
250	250	16	11	160		753 221 032	9.700	2 51 301 004

d	L	L1	L2	L3	e	e1
(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)
63	65	70	25	25	5.8	2,9
63	65	70	25	25	5.8	4,6
75	70	75	25	25	6.8	2,9
75	70	75	25	25	6.8	4,6
75	70	75	25	25	6.8	5,8
90	80	85	25	25	8.2	4,6
90	80	85	25	25	8.2	5,8
90	80	85	25	25	8.2	6,8
110	90	95	30	25	10.0	2,9
110	90	95	30	25	10.0	4,6
110	90	95	30	25	10.0	5,8
110	90	95	30	25	10.0	6,8
110	90	95	30	25	10.0	8,2
160	142	135	50	30	14.6	5,8
160	142	135	50	30	14.6	6,8
160	142	135	50	30	14.6	8,2
160	142	135	50	30	14.6	10,0
225	155	165	40	30	20.5	8,2
225	155	165	40	30	20.5	10,0
225	155	165	40	30	20.5	14,6
250	228	197	140	37	22.7	10,0
250	229	219	117	60	22.7	14,6

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>