




ecoFIT T 90° egal PE100
d50-500mm / SDR17/17.6

Ausführung:

- Werkstoff: PE100
- Konventionelle Stumpfschweissung nach DVS 2207
- IR = Infrarot (IR Plus) kompatibel. Zu verschweissen mit Parameter PE100



d	DN	PN	SDR	SM	Code	Gewicht	L	L1	e
(mm)	(mm)	(bar)				(kg)	(mm)	(mm)	(mm)
50	40	10	17/17.6	IR	753 208 510	0.136	90	57	2.9
63	50	10	17/17.6	IR	753 208 511	0.187	107	64	3.6
75	65	10	17/17.6	IR	753 208 412	0.232	74	20	4.8
90	80	10	17/17.6	IR	753 208 413	0.408	90	20	5.6
110	100	10	17/17.6	IR	753 208 414	0.724	110	20	6.9
125	100	10	17/17.6	IR	753 208 515	1.169	125	52	7.1
140	125	10	17/17.6	IR	753 208 516	1.805	157	62	8.0
160	150	10	17/17.6	IR	753 208 517	2.375	160	57	9.1
180	150	10	17/17.6	IR	753 208 518	4.095	214	96	10.2
200	200	10	17/17.6	IR	753 208 519	5.145	220	93	11.4
225	200	10	17/17.6	IR	753 208 520	7.140	225	76	12.8
250	250	10	17/17.6		753 208 521	7.670	225	67	14.2
280	250	10	17/17.6		753 208 522	10.900	264	86	15.9
315	300	10	17/17.6		753 208 523	14.870	282	87	17.9
355	350	10	17/17.6		753 208 524	21.800	345	105	21.1
400	400	10	17/17.6		753 208 525	28.600	365	105	23.7
450	450	10	17/17.6		753 208 526	42.400	425	135	26.7
500	500	10	17/17.6		753 208 527	57.600	470	155	29.7

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>