




ecoFIT Winkel 45° PE100

Ausführung:

- Konventionelle Stumpfschweissung nach DVS 2207
- IR = Infrarot (IR Plus) kompatibel. Zu verschweissen mit Parameter PE100



d	DN	PN	SDR	SM	Code	Gewicht	Z	Q1	s1
(mm)	(mm)	(bar)				(kg)	(mm)	(mm)	(mm)
20	15	16	11	IR	753 158 606	0.007	8	24	1.9
25	20	16	11	IR	753 158 607	0.013	9	25	2.3
32	25	16	11	IR	753 158 608	0.019	11	25	2.9
40	32	16	11	IR	753 158 609	0.036	14	25	3.7
50	40	16	11	IR	753 158 610	0.059	16	26	4.6
63	50	16	11	IR	753 158 611	0.103	18	29	5.8
75	65	16	11	IR	753 158 612	0.146	20	29	6.8
90	80	16	11	IR	753 158 613	0.241	23	34	8.2
110	100	16	11	IR	753 158 614	0.442	27	43	10.0
125	100	16	11	IR	753 158 615	0.638	31	48	11.4
140	125	16	11	IR	753 158 616	0.902	33	55	12.7
160	150	16	11	IR	753 158 617	1.340	40	60	14.6
200	200	16	11	IR	753 158 619	2.612	49	75	18.2
225	200	16	11	IR	753 158 620	3.638	55	85	20.5

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>