



Festflansch PP-H metrisch
Kombinierte Dichtfläche: flach und gerillt

Ausführung:

- Anschlussmasse nach ISO 7005 PN 10, EN 1092 PN 10, DIN 2501 PN 10, BS 4504 PN 10
- Mit Schweissmuffe metrisch
- Werkstoff: PP-H

AL: Anzahl der Bohrungen

d	Zoll	DN	PN	Code	SP	Gewicht
(mm)	(inch)	(mm)	(bar)			(kg)
20	1/2	15	10	727 740 106	0	0.065
25	3/4	20	10	727 740 107	0	0.074
32	1	25	10	727 740 108	0	0.115
40	1 1/4	32	10	727 740 109	0	0.175
50	1 1/2	40	10	727 740 110	0	0.210
63	2	50	10	727 740 111	0	0.286

d	D1	D2	D3	D4	H	H1	AL	z
(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)		(mm)
20	27	65	94	14	12	19	4	5
25	33	75	103	14	13	21	4	5
32	40	85	115	14	14	23	4	5
40	50	100	138	18	15	25	4	5
50	61	110	148	18	16	27	4	5
63	76	125	163	18	18	31	4	5

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>