



## PROGEF Standard Übergangs-Muffe Metrisch Rp (PN10)

### Ausführung:

- Material: PP-H
- Mit Schweissmuffe metrisch und zylindrischem Rohr-Innengewinde Rp, verstärkt
- Verstärkungsring rostfrei (A2)
- Anschluss nur für Kunststoff- oder Metallgewinde
- Keine PP-schädigenden Gewindedichtpasten verwenden
- Auf spannungsarme Montage achten und grosse Temperaturwechsel vermeiden

| d    | Gewindetyp | Zoll   | PN    | Code               | SP | Gewicht | L    | s    | z    |
|------|------------|--------|-------|--------------------|----|---------|------|------|------|
| (mm) |            | (inch) | (bar) |                    |    | (kg)    | (mm) | (mm) | (mm) |
| 20   | Rp         | ¾      | 10    | <b>727 910 205</b> | 10 | 0.017   | 35   | 32   | 7    |
| 20   | Rp         | ½      | 10    | <b>727 910 206</b> | 10 | 0.018   | 40   | 32   | 7    |
| 25   | Rp         | ¾      | 10    | <b>727 910 207</b> | 10 | 0.025   | 42   | 36   | 7    |
| 32   | Rp         | 1      | 10    | <b>727 910 208</b> | 10 | 0.040   | 48   | 46   | 7    |
| 40   | Rp         | 1 ¼    | 10    | <b>727 910 209</b> | 10 | 0.064   | 53   | 55   | 7    |
| 50   | Rp         | 1 ½    | 10    | <b>727 910 210</b> | 10 | 0.089   | 54   | 65   | 9    |
| 63   | Rp         | 2      | 10    | <b>727 910 211</b> | 20 | 0.144   | 62   | 80   | 9    |

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: [info.ps@georgfischer.com](mailto:info.ps@georgfischer.com)

Internet: <http://www.gfps.com>