




Winkel 90° PVC-C metrisch Rp

Ausführung:

- Mit Klebemuffe metrisch und zylindrischem Rohr-Innengewinde Rp
- Verstärkungsring rostfrei (A2)
- Anschluss nur für Kunststoff- oder Metallgewinde
- Auf spannungsarme Montage achten und grosse Temperaturwechsel vermeiden
- Keine PVC-C schädigenden Gewindedichtpasten verwenden



Rp (inch)	d (mm)	PN (bar)	Code	SP	Gewicht (kg)	z1 (mm)	z2 (mm)	D (mm)	L (mm)
½	20	16	723 100 206	10	0.024	11	14	30	27
¾	25	16	723 100 207	10	0.037	14	17	35	33
1	32	16	723 100 208	10	0.063	17	22	45	39
1 ¼	40	16	723 100 209	10	0.134	23	27	55	50
1 ½	50	16	723 100 210	5	0.199	27	36	62	58
2	63	16	723 100 211	10	0.337	33	46	75	73

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>