



Übergangsverschraubung PVC-U/Messing metrisch R

Ausführung:

- Überwurfmutter: PVC-U
- Einschraubteil: PVC-U-Klebhempe metrisch
- Einlegteil: Messing mit konischem Rohr-Aussengewinde R
- Dichtung: O-Ring EPDM Nr. 748 410 006-014; d90 748 410 248

d	Gewindetyp	Zoll	PN	Code	SP	Gewicht
(mm)		(inch)	(bar)			(kg)
20	R	½	16	721 550 906	10	0.125
25	R	½	16	721 550 957	5	0.196
25	R	¾	16	721 550 907	5	0.196
25	R	1	16	721 550 967	5	0.307
32	R	½	16	721 550 958	5	0.297
32	R	¾	16	721 550 968	5	0.297
32	R	1	16	721 550 908	5	0.283
40	R	1 ¼	16	721 550 909	2	0.502
50	R	1 ½	16	721 550 910	2	0.681
63	R	2	16	721 550 911	2	1.101
75	R	2 ½	10	721 550 912	2	1.706
90	R	3	10	721 550 913	1	2.662

d	D	L	L1	L2	z	G	s
(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(inch)	(mm)
20	43	63	37	26	47	1	25
25	51	66	37	29	47	1 1/4	30
25	51	71	42	29	52	1 1/4	30
25	51	75	46	29	56	1 1/4	30
32	58	70	37	33	48	1 1/2	36
32	58	75	42	33	53	1 1/2	36
32	58	79	46	33	57	1 1/2	36
40	72	91	52	39	65	2	46
50	83	102	56	46	71	2 1/4	55
63	100	125	67	58	87	2 3/4	65
75	127	139	77	62	95	Tr 108x5	85
90	150	155	86	69	104	Tr 125x8	95

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>