



Anschlusssteil 546 und 543 PVC-U (G06) Mit Gewindemuffe Rp

Ausführung:

- Anschluss nur für Kunststoffgewinde
- Keine PVC-U schädigenden Gewindedichtpasten verwenden

Rp	PN	Code	SP	Gewicht	z	D1	D	L	L1
(inch)	(bar)			(kg)	(mm)	(mm)	(mm)	(mm)	(mm)
3/8	10	161 490 690	1	0.011	7	24	38	20	4
1/2	10	161 490 691	1	0.013	6	28	38	22	4
3/4	10	161 490 692	1	0.019	7	34	44	25	5
1	10	161 490 693	1	0.031	7	42	53	28	5
1 1/4	10	161 490 694	1	0.047	7	52	65	30	5
1 1/2	10	161 490 695	1	0.074	9	63	77	32	6
2	10	161 490 696	1	0.129	10	78	99	38	7
2 1/2	10	161 490 697	1	0.255	18	92	125	49	9
3	10	161 490 698	1	0.436	23	110	150	57	10
4	10	161 490 699	1	0.645	29	134	180	69	11

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>