



Behälteranschluss Typ 050 PVC-U metrisch mit O-Ring

Ausführung:

- Dichtungen: O-Ring EPDM, Flachdichtung EPDM
- Gleitring: PP
- Entleerungsbohrungen: zwei Bohrungen im Sechskantkopf
- Für runde Tanks

d (mm)	PN (bar)	Code	SP	Gewicht (kg)
16	16	161 050 385	1	0.040
20	16	161 050 386	1	0.070
25	16	161 050 387	1	0.160
32	16	161 050 388	1	0.200
40	16	161 050 389	1	0.240
50	16	161 050 390	1	0.400
63	16	161 050 391	1	0.530

D	G	d2	D1	S	L3	Bohrung	S1	L4	L	L2	L1	D
(mm)	(inch)	(mm)	(mm)	(mm)	max (mm)	in Behälterwand (mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)
16	¾	5	29	32	19	28	40	14	77	11	58	44
20	1	5	35	40	17	35	50	16	83	12	61	54
25	1 ¼	5	42	50	18	43	55	19	90	13	65	60
32	1 ½	5	49	56	19	49	65	22	95	13	67	69
40	2	5	59	69	16	61	80	26	104	13	72	84
50	2 ¼	5	70	76	16	67	85	31	113	15	76	92
63	2 ¾	5	82	95	19	83	100	38	128	15	84	108

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>