



Behälteranschluss Typ 050 PVC-U Reduzierte Muffe metrisch

Ausführung:

- Dichtungen: Flachdichtungen EPDM
- Gleitring: PP
- Entleerungsbohrungen: zwei Bohrungen im Sechskantkopf
- FKM Flachdichtungen erhältlich für Tank Adapter Typ 050

d (mm)	PN (bar)	d1 (mm)	EPDM Code	SP	Gewicht (kg)
16	16	12	161 050 345	1	0.068
20	16	16	161 050 346	1	0.102
25	16	20	161 050 347	1	0.157
32	16	25	161 050 348	1	0.220
40	16	32	161 050 349	1	0.353
50	16	40	161 050 350	1	0.438
63	16	50	161 050 351	1	0.680

d (mm)	L (mm)	D (mm)	L1 (mm)	L5 (mm)	L4 (mm)	S1 (mm)	L2 (mm)	S (mm)	D1 (mm)	Bohrung in Behäl- terwand (mm)	L3 max (mm)	G (inch)	d2 (mm)
16	96	44	58	12	14	40	11	32	29	28	19	¾	5
20	104	54	61	14	16	50	12	40	35	35	17	1	5
25	112	60	65	16	19	55	13	50	42	43	18	1 ¼	5
32	119	69	67	19	22	65	13	56	49	49	19	1 ½	5
40	132	84	72	22	26	80	13	69	59	61	16	2	5
50	145	92	76	26	31	85	15	76	70	67	16	2 ¼	5
63	163	108	84	31	38	100	15	95	82	83	19	2 ¾	5

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>