




Kugelhahn Typ 546 Pro PVC-U Mit Klebemuffen metrisch

Ausführung:

- Serienmässig abschliessbar (DN10-DN50)
- Leicht ein- und ausbaubar
- Kugeldichtung PTFE
- Integrierte Gewindebuchsen für die Befestigung der Armatur
- z-Mass, Anschlusssteil und Überwurfmutter **sind kompatibel** zu Typ 546 (1. Generation)

Option:

- Schnittstellenmodul mit Positionsrückmeldung, inkl. LED Sensor (DN10-50)
- Manuelle Federrückstelleinheit ("Dead man") (DN10-25)
- Stellantriebe pneumatisch und elektrisch von Georg Fischer
- Armatur individuell konfigurierbar
- Multifunktions-Modul mit integrierten Endschaltern (DN65-100)

d (mm)	DN (mm)	Zoll (inch)	PN (bar)	kv-Wert ($\Delta p=1$ bar) (l/min)	EPDM Code	SP	Gewicht (kg)	FKM Code	SP	Gewicht (kg)
16	10	3/8	16	71	161 546 061	1	0.153	161 546 071	1	0.156
20	15	1/2	16	185	161 546 062	1	0.156	161 546 072	1	0.158
25	20	3/4	16	350	161 546 063	1	0.240	161 546 073	1	0.242
32	25	1	16	700	161 546 064	1	0.343	161 546 074	1	0.345
40	32	1 1/4	16	1000	161 546 065	1	0.610	161 546 075	1	0.615
50	40	1 1/2	16	1600	161 546 066	1	0.838	161 546 076	1	0.844
63	50	2	16	3100	161 546 067	1	1.537	161 546 077	1	1.552
75	65	2 1/2	16	5000	161 546 068	1	4.343	161 546 078	1	3.563
90	80	3	16	7000	161 546 069	1	6.184	161 546 079	1	5.376
110	100	4	16	11000	161 546 070	1	8.642	161 546 080	1	11.600

d (mm)	D (mm)	H (mm)	H1 (mm)	H2 (mm)	L (mm)	L1 (mm)	L2 (mm)	L4 (mm)	L5 (mm)	L6 (mm)	M	z (mm)
16	50	61	27	12	92	82	56	25	35	47	M6	64
20	50	61	27	12	95	82	56	25	35	47	M6	64
25	58	74	30	12	110	106	65	25	44	62	M6	72
32	68	80	36	12	123	106	71	25	44	62	M6	79
40	84	95	44	15	146	131	85	45	57	74	M8	94
50	97	102	51	15	157	131	89	45	57	74	M8	95
63	124	117	64	15	183	152	101	45	66	86	M8	107
75	166	150	85	15	233	270	136	70	64	206	M8	144
90	200	161	105	15	255	270	141	70	64	206	M8	151
110	238	178	123	22	301	320	164	120	64	256	M12	174

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>