



SYGEF Standard Übergangsmuffe Innengewinde Rp PN16

Ausführung:

- Material: PVDF
- Mit Schweissmuffe und zylindrischem Innengewinde
- Anschluss nur für Kunststoffgewinde
- Keine PVDF-schädigenden Gewindedichtpasten verwenden
- Spannungsarm montieren und grosse Temperaturschwankungen vermeiden

d	Gewindetyp	Zoll	PN	Code	NPK	Gewicht	L	s	z
(mm)		(inch)	(bar)			(kg)	(mm)	(mm)	(mm)
20	Rp	½	16	735 910 206	434 452	0.030	34	32	5
25	Rp	¾	16	735 910 207	434 453	0.036	38	36	6
32	Rp	1	16	735 910 208	434 454	0.067	43	46	7
40	Rp	1 ¼	16	735 910 209	434 455	0.100	47	55	7
50	Rp	1 ½	16	735 910 210	434 456	0.135	54	65	9
63	Rp	2	16	735 910 211	434 457	0.217	62	80	9

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
info.ps@georgfischer.com Internet: <http://www.gfps.com>