



SYGEF Plus Winkel 45° SDR21/PN16
High Purity clean-room product ISO Class 5 (100)

Ausführung:

- Werkstoff: PVDF-HP

d	PN	SDR	SM	Code	Gewicht	e	L	L1
(mm)	(bar)				(kg)	(mm)	(mm)	(mm)
20	16	21	WNF, IR	735 158 631	0.015	1.9	32	25
25	16	21	WNF, IR	735 158 632	0.019	1.9	34	26
32	16	21	WNF, IR	735 158 633	0.033	2.4	36	26
40	16	21	WNF, IR	735 158 634	0.048	2.4	39	28
50	16	21	WNF, IR	735 158 635	0.077	3.0	42	30
63	16	21	WNF, IR	735 158 636	0.111	3.0	47	31
75	16	21	WNF, IR	735 158 637	0.198	3.6	49	32
90	16	21	WNF, IR	735 158 638	0.279	4.3	57	37
110	16	21	WNF, IR	735 158 639	0.506	5.3	70	46
140	16	21	IR	735 158 641	1.095	6.7	88	57
160	16	21	IR	735 158 642	1.605	7.7	100	62
200	16	21	IR	735 158 644	3.018	9.6	124	77
225	16	21	IR	735 158 645	4.324	10.8	140	88

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>